



外形尺寸 Shell size	YL16-2	YL16-3	YL16-4	YL16-5	YL16-6	YL16-7	YL16-8	YL16-9	YL16-10
	正装 反装	正装 反装	正装 反装	正装 反装	正装 反装	正装 反装	正装 反装	正装 反装	正装 反装
接触对排列分布 从针的方向看 Contact Arrangements Comply with the needle direction									
额定电流/电压 Rated current/voltage	7A-125V	7A-125V	5A-125V	5A-125V	4A-125V	4A-125V	4A-125V	4A-125V	4A-125V
工作电压 (AC, V) 分钟 Operatin limit voltage(AC, V.rms)	200	200	200	200	200	200	200	200	200
耐电压 (AC, V) 1分钟 Withstanding voltage (AC, V.rms) 1minute	1500	1500	1500	1500	1500	1500	1500	1500	1500
绝缘阻抗 (MΩ) DV500V Insulation resistance(MΩ MIX.) At DC 500V	1500	1500	1500	1500	1500	2000	2000	2000	2000
接触阻抗 (MΩ) DC1A Contact resistance(MΩ MIX.) AT DC 1A	10	10	10	10	10	10	10	10	10
接触对孔径 φ(mm) Soidre inter diameter	2.45	2.45	2.45	2	1.15	1.15	1.15	1.15	1.15